Wastewater Management Section

List of Registered Sewage Tanks

As Established in Chapter 246-272C WAC

January 1, 2013



For more information or additional copies of this document contact:

Wastewater Management Section

Washington State Department of Health

Physical address: 243 Israel Road SE, Tumwater, WA 98501 Mailing address: PO Box 47824, Olympia, WA 98504-7824

Phone: (360) 236-3330 FAX: (360) 236-2257

Email: wastewatermanagement@doh.wa.gov

Secretary of Health Mary Selecky

For persons with disabilities, this document is available upon request in other formats. To submit a request, please call 1-888-586-9427 (TDD/TTY 1-800-833-6388).

Para personas discapacitadas, este documento está disponible a su pedido en otros formatos. Para hacer su pedido llame al 1-888-586-9427 (TDD/TTY 1-800-833-6388).

DOH 337-046

Contents

| Introduction and Overview | 3 |
|---|----|
| List of Manufacturers of Registered Sewage Tanks – Concrete Tanks | 4 |
| List of Manufacturers of Registered Sewage Tanks – Non-Concrete Tanks | 39 |

NOTE: The presence of a product on this list does not constitute approval of marketing, advertising, or labeling practices employed by manufacturer, nor is it an affirmation of manufacturer claims of product performance. Registration listing does not constitute endorsement of these products by the Washington State Department of Health. Information obtained from the sources listed is the sole responsibility of the manufacturer or other provider.

Updates this revision:

| Manufacturer | Model(s) Number | Approved |
|------------------------------|--------------------------------|-------------------|
| Orenco Systems, Inc | 24 & 30 Inch Pump Basins | November 1, 2012 |
| Berts Excavating and Precast | 1250 & 1500 | December 4, 2012 |
| Berg Vault Company | Amended 1000, 1250 and 1500 | December 19, 2012 |
| | | |
| | | |

Updates this revision also include 2012 Renewals.

DOH 337-046 Page 2 of 47

Introduction and Overview

Chapter 246-272C WAC establishes sewage tank design and construction requirements, plan review and approval requirements, and prefabricated tank registration requirements. This chapter applies to all prefabricated tanks and all cast-in-place tanks. When the Washington State Department of Health (DOH) has determined that a product meets the registration requirements that are established in the rule, the product will be placed on the "List of Registered Sewage Tanks." This document is a revision to the previous edition of the "List of Registered Sewage Tanks."

Overview

Chapter 246-272C WAC On-Site Sewage System Tanks took full effect on December 19, 2009.

- 1. A prefabricated tank manufacturer or agent shall comply with the registration requirements of Chapter 246-272C-0130 WAC.
- 2. DOH or the local health officer shall only allow use of prefabricated sewage tanks from the "List of Registered Sewage Tanks."
- 3. All prefabricated tank renewal registrations expire on December 31st of the third year of registration.
- 4. All prefabricated tank renewal applications must be received by the department no later than October 31st of the year the registration expires.

We welcome suggestions to improve this document. If you identify an error or have an idea about how to improve the usefulness of this document, please contact us at wastewatermanagement@doh.wa.gov.

For questions regarding sewage tank standards or information about application for product review and approval, please contact Jeanne Andreasson, P.E. at (360) 236-3360 or Jeanne.Andreasson@doh.wa.gov.

DOH 337-046 Page 3 of 47

List of Manufacturers of Registered Sewage Tanks – Concrete Tanks

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|----------------------------------|-----------------|---------------------|------------------------|----------------------|-----------------------|---|
| A-1 Redi Mix | 1000 S & SP | 1024 | One / Two | Septic Tank, Pump | 2-8-2012 / | 3' of soil cover, maximum |
| P.O. Box 891 Ilwaco, WA 98624 | | | | Tank, Holding Tank | 12-31-2014 | high water table to top of lid. |
| | | | | & Trash Tank | | |
| 360-642-3153 | 1500 S | 1643 | Two | Septic Tank, Holding | 2-8-2012 / | 3' of soil cover, maximum |
| 360-642-3345 (fax) | | | | Tank & Trash Tank | 12-31-2014 | high water table to top of lid. |
| | 1500 | 2012 | One | M31 Glendon Basin | 2-8-2012 / | Containment tank for the |
| | Glendon | | | | 12-31-2014 | M31 Glendon BioFilter |
| | | | | | | treatment unit (120 GPD). |
| | | | | | | Follow installation |
| | | | | | | instruction. |
| Berg Vault Company | 400 | 355 | One | Septic Tank, Pump | 7-8-2010 / | 3' of soil cover, maximum |
| P. O. Box 1205 | | | | Tank, Holding Tank | 12-31-2015 | high water table to top of lid. |
| Mount Vernon, WA 98273 | | <u> </u> | | & Trash Tank | | |
| 360-424-4999 | 400-T | 355 | One | Septic Tank, Pump | 7-8-2010 / | Maximum water table at |
| 360-424-5839 (fax) | | | | Tank, Holding Tank | 12-31-2015 | ground level. HS20-44 traffic |
| | | | | & Trash Tank | | rating. Must have traffic rated risers and lid. |
| | 750 | 748 | One | Septic Tank, Pump | 7-8-2010 / | 3' of soil cover, maximum |
| | | | | Tank, Holding Tank | 12-31-2015 | high water table to top of lid. |
| | | | | & Trash Tank | | |
| | 750-T | 748 | One | Septic Tank, Pump | 7-8-2010 / | Maximum water table at |
| | | | | Tank, Holding Tank | 12-31-2015 | ground level. HS20-44 traffic |
| | | | | & Trash Tank | | rating. Must have traffic rated risers and lid. |
| | 1000 P | 1047 | One | Septic Tank, Pump | 7-8-2010 / | 3' of soil cover, maximum |
| | 10001 | 104/ | | Tank, Holding Tank | 12-31-2015 | high water table to top of lid. |
| | | | | & Trash Tank | 12 31 2013 | mgn water table to top of fid. |

DOH 337-046 Page 4 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--------------------------------|------------------------|---------------------|------------------------|--|--------------------------|--|
| Berg Vault Company (continued) | 1000 P-T | 1047 | One | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 7-8-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000 S, P & G | 1049 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank & MicroFast 0.5 | 7-8-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 S-T, P-T & G-T | 1049 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank & MicroFast 0.5 | 7-8-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 S & P | 1348 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank & MicroFast 0.5, 0.75 and 0.9 | 7-8-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T & P-T | 1348 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank & MicroFast 0.5, 0.75 and 0.9 | 7-8-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 5 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--------------------------------|-------------------|---------------------|------------------------|--|----------------------------|--|
| Berg Vault Company (continued) | 1500 S & P | 1562 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank, AdvanTex Processing Tank & MicroFast 0.5, 0.75 and 0.9 | 7-8-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500 S-T & P-T | 1562 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank, AdvanTex Processing Tank & MicroFast 0.5, 0.75 and 0.9 | 7-8-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750 S & P | 1772 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 5-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1750 S-T & P-T | 1772 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 5-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | DF50 | 909 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | DF60 | 1138 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | M31 Basin JR | 2070 | One | Glendon BioFilter Model M-31 Basin | 4-13-2011 / 12/31/2013 | Follow installation instructions. |

DOH 337-046 Page 6 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--------------------------------|-----------------------------------|---------------------|------------------------|--|---------------------------|--|
| Berg Vault Company (continued) | TRD 1000 C & TRD 1250 | | Two | TRD Systems | 7-28-2011 / 12/31/2013 | 3' of soil cover, maximum high water table to top of lid. |
| | TRD 1000 C - T & TRD 1250 T | | Two | TRD Systems | 7-28-2011 / 12/31/2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 800 P | 808 | One | Pump Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 800 P-T | 808 | One | Pump Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000 S, P & G | 1035 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 /12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 S-T, P- T & G-T | 1035 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 S, P & G | 1278 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T, P- T & G-T | 1278 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 7 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--------------------------------|-------------------------|---------------------|------------------------|--|---------------------------|--|
| Berg Vault Company (continued) | 1500 S, P & G | 1540 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500 S-T, P- T & G-T | 1540 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 AdvanTex | 1540 | Two | AdvanTex Processing Tank | 6-23-2011 / 12-31-2013 | 4' of soil cover, maximum high water table to top of lid. |
| | 1500 AdvanTex-T | 1540 | Two | AdvanTex Processing Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750 S, P & G | 1779 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1750 S-T, P- T & G-T | 1779 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 3000 S, P & G | 3042 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 8 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-------------------------|----------------------------|----------------------------|--|---------------------------|---|
| Berg Vault Company (continued) | 3000 S-T, P- T & G-T | 3042 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 6-23-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Berts Excavating And Precast P.O. Box 73 Sunnyside, WA 98944 509-837-2117 509-837-6282 (fax) | 1000 | 1000 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 6-26-2012 / 12-31-2014 | 3' of soil cover. Water table must be three feet below top of tank, otherwise tank will be susceptible to buoyancy effects. |
| | 1250 | 1250 | One / Two | Septic Tank, Pump Tank, Holding Tank | 12-4-2012 / 12-31-2014 | 12" minimum and 36" maximum soil cover. Water table must be three feet below top of tank, otherwise tank will be susceptible to buoyancy effects. |
| | 1500 | 1500` | One / Two / Three | Septic Tank, Pump Tank, Holding Tank | 12-4-2012 / 12-31-2014 | Maximum 3' of soil cover. Water table must be three feet below top of tank, otherwise tank will be susceptible to buoyancy effects. |
| Bode's Precast, Inc. 1861 E. Pole Rd. Everson, WA 98247 | 300 S / 300 P | 324 (septic) 338 (pump) | One | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, water table at ground level. |
| 360-354-3912 360-354-0360 (fax) www.BodesPrecast.com | 500 S / 500 P | 471 | One | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, water table at ground level. |
| | 750 S / 750 P | 761(septic) 797 (pump) | Two (septic) One (pump) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, water table at ground level. |

DOH 337-046 Page 9 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|----------------------------------|-------------------------|------------------------------|----------------------------|--|---------------------------|--|
| Bode's Precast, Inc. (continued) | 1000 S / 1000 GI | 998 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 S-T / 1000 GI-T | 998 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000 P | 1033 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 P-T | 1033 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 S / 1250 P | 1297 (septic) 1316 (pump) | Two (septic) One (pump) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T / 1250 P-T | 1297 (septic) 1316 (pump) | Two (septic) One (pump) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 S / 1500 GI | 1537 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500 S-T / 1500 GI-T | 1537 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 P | 1579 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 10 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|----------------------------------|-------------------------|-------------------------------|------------------------|--|----------------------------|--|
| Bode's Precast, Inc. (continued) | 1500 P-T | 1579 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750 S / 1750 GI | 1840 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1750 S-T / 1750 GI-T | 1840 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750 P | 1881 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1750 P-T | 1881 | One | Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750 PS Combo | 1018 (septic) & 788 (pump) | Three | Septic / Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1750 PS-T Combo | 1018 (septic) & 788 (pump) | Three | Septic / Pump Tank, Holding Tank and Trash Tank | 10-5-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | DF50 | 841 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | M31 Basin | 1993 | One | Glendon BioFilter Model M-31 Basin | 5-5-2011 / 12-31-2015 | Follow installation instructions. |

DOH 337-046 Page 11 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-------------------------|---------------------|-------------------------|---|---------------------------|--|
| Cascade Concrete Products Company, Inc. P.O. Box 387 | 1000 S & P | 1066 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-16-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| 54 Horizon Flats Road Winthrop, WA 98862 509-996-2435 | 1000 S-T & P-T | 1066 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-16-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 S | 1284 | Two | Septic Tank, Holding Tank & Trash Tank | 8-16-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T | 1284 | Two | Septic Tank, Holding Tank & Trash Tank | 8-16-2011 /12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Colville Valley Concrete Corporation | 500 P | 504 | One | Pump Tank, Holding Tank & Trash Tank | 9-13-2011 / 12-31-2013 | 3' of soil cover, maximum water table at ground level. |
| P.O. Box 343 Colville, WA 99114 509-684-2534 509-684-7635 (fax) | 1000 S, P & G | 1022 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 9-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 S-T, P- T & G-T | 1022 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 9-13-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 S, P, G & SP | 1561 1538 (SP) | One / Two Three (SP) | Septic Tank, Pump Tank, Grease Interceptor Tank, Septic / Pump Tank, Holding Tank & Trash Tank | 9-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 12 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------------------------|---------------------|-------------------------|---|---------------------------|--|
| Colville Valley Concrete (continued) | 1500 S-T, P- T, G-T & SP- T | 1561 1538 (SP) | One / Two Three (SP) | Septic Tank, Pump Tank, Grease Interceptor Tank, Septic / Pump Tank, Holding Tank & Trash Tank | 9-13-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Cotton Redi-Mix P.O. Box 179 Port Hadlock, WA 98339 360-385-0480 360-379-6892 (fax) | Cotton 1000 | 1060 /1008 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 3-8-2011 / 12-31-2013 | 3' of soil cover, maximum water table at ground level. |
| cottonshold@yahoo.com | Cotton 1500 | 1620 / 1563 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 3-8-2011 / 12-31-2013 | 3' of soil cover, maximum water table at ground level. |
| | Cotton Glendon M-31 | 1998 | One | Glendon BioFilter Model M-31 Basin | 3-8-2011 / 12-31-2013 | Follow installation instructions. |
| Cuz Concrete Products, Inc. 19604 67 th Ave. NE Arlington, WA 98223 360-435-5531 | 818 | 5085 | Two or Three | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-13-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| 360-435-8575 (fax) | 500P | 542 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 500P-T | 542 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 750P | 781 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 13 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|-----------------------|---------------------|------------------------|--|---------------------------|--|
| Cuz Concrete Products, Inc. (continued) | 750P-T | 781 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000S / 1000GI | 1021 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1000S-T / 1000GI-T | 1021 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000P | 1059 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1000P-T | 1059 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250S / 1250GI | 1257 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1250S-T / 1250GI-T | 1257 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250P | 1304 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1250P-T | 1304 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 14 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|-----------------------|---------------------|------------------------|--|---------------------------|--|
| Cuz Concrete Products, Inc. (continued) | 1750S / 1750GI | 1814 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 /12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1750S-T / 1750GI-T | 1814 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1750P | 1874 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 1750P-T | 1874 | One | Pump Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 3000S / 3000GI | 3042 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 3000S-T / 3000GI-T | 3042 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 3000P | 3105 | One | Pump Tank, Holding Tank & Trash Tank. | 7-19-2010 / 12-31-2015 | 4' of soil cover, maximum high water table to top of lid. |
| | 3000P-T | 3105 | One | Pump Tank, Holding Tank & Trash Tank. | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | Fast ATU | 1653 | Two | Fast 0.5 ATU Tank Fast 0.75 ATU Tank Micro FAST Bio- Barrier | 7-19-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 15 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|-----------------------|---------------------|------------------------|--|----------------------------|---|
| Cuz Concrete Products, Inc. (continued) | Fast ATU-T | 1653 | Two | Fast 0.5 ATU Tank Fast 0.75 ATU Tank Micro FAST Bio- Barrier | 7-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500S / 1500GI | 1500 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-14-2012 / 12-31-2014 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500S-T / 1500GI-T | 1500 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-14-2012 / 12-31-2014 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500P | 1500 | One | Pump Tank, Holding Tank & Trash Tank | 8-14-2012 / 12-31-2014 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500P-T | 1500 | One | Pump Tank, Holding Tank & Trash Tank | 8-14-2012 / 12-31-2014 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| D&K Concrete Products Inc. 15008 NE 15 th Avenue Vancouver, WA 98685 | 660P | 685 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| 360-573-4020 dkconcrete@gmail.com | 1000P | 1059 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid |
| | 1000P-T | 1059 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250P | 1315 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 16 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|----------------------------|----------------------|------------------------|---|----------------------------|---|
| D&K Concrete Products Inc. (continued) | 1250P-T | 1315 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500P | 1543 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500P-T | 1543 | One | Pump Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1000ST 1250ST 1500ST | 1000 1250 1500 | Two | Septic Tank, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 15" minimum soil cover. 3' maximum soil cover. Maximum high water table to top of lid. |
| | 1860 SP | 1581 | Three | Septic Tank / Pump Tank Combo, Holding Tank & Trash Tank | 10-28-2012 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| Ecological Tanks, Inc. 2247 Hwy. 151 North Downsville, LA 71234 | AS500-C | 1000 | | Aqua Safe AS500 | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| 318-644-0397 318-644-7257 (fax) aquasafe@bayou.com | AS600-C | 1190 | | Aqua Safe AS600 | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS750-C | 1516 | | Aqua Safe AS750 | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS1000-C | 2008 | | Aqua Safe AS1000 | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |

DOH 337-046 Page 17 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|---|---------------------------|--|
| Ecological Tanks, Inc. (continued) | AS500L-C | 908 | _ | Aqua Safe AS500L | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS600L-C | 1058 | | Aqua Safe AS600L | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS800L-C | 1516 | | Aqua Safe AS800L | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS1100L-C | 2008 | | Aqua Safe AS1100L | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| | AS600+5NR-C | 1000 | | Aqua Safe AS600+4NR | 9-27-2010 / 12-31-2015 | Maximum amount of cover should be no greater than 18". No ground water. |
| Evergreen Precast P. O. Box 58 | 1250 SDC | 1260 | Two | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| Sumner, WA 98390 253-863-6510 253-863-2901 (fax) | 1250 SDC-T | 1260 | Two | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 SSC | 1236 | One | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 SSC-T | 1236 | One | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500P | 1569 | One | Pump Tank | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 18 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|-------------------------------|-----------------|---------------------|------------------------|--|----------------------------|--|
| Evergreen Precast (continued) | 1500P-T | 1569 | One | Pump Tank | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1600 SDC | 1595 | Two | Septic Tank, Holding Tank, Trash Tank & MicroFAST Models 0.5 and 0.75 Tanks | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1600 SDC-T | 1595 | Two | Septic Tank, Holding Tank, Trash Tank & MicroFAST Models 0.5 and 0.75 Tanks | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1600SSC | 1637 | One | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1600SSC-T | 1637 | One | Septic Tank, Holding Tank and Trash Tank | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1900P | 1951 | One | Pump Tank | 6-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1900P-T | 1951 | One | Pump Tank | 6-22-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | DF50 | 909 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | DF60 | 1070 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | DF50-2 | 1466 | Two | Delta Whitewater DF Series with Pump Chamber | 12-10-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 19 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|--------------------------|---------------------|------------------------|--|----------------------------|--|
| Evergreen Precast (continued) | DF50-2-HW | 1466 | Two | Delta Whitewater DF Series with Pump Chamber | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | EP 300-1 / EP 300-2 | 3000 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank, and AdvanTex Processing Tank | 4-13-2012 / 12-31-2014 | 3' of cover, maximum high water table to top of lid. |
| | EP 300-1T / EP 300-2T | 3000 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank, and AdvanTex Processing Tank | 4-13-2012 / 12-31-2014 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Godbey Red-E-Mix Concrete P.O. Box 505 Brewster, WA 98812 509-689-2415 509-689-2041 (fax) | 1000 | 1013 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 4-27-2012 / 12-31-2014 | 3' of soil cover, water table at lid. |
| | 1250 | 1258 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 4-27-2012 / 12-31-2014 | 3' of soil cover, water table at lid. |

DOH 337-046 Page 20 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|------------------------------------|----------------------|------------------------|--|----------------------------|--|
| H2 Precast Inc. 3835 N. Clemons Street East Wenatchee, WA 98802 509-884-6644 | H2PC- 3000, 3500, 4000 | 3000 3500 4000 | One / Two | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. |
| 509-884-0044 509-884-4567 (fax) H2precast.com cprewitt@h2precast.com | H2PC- 3000T, 3500,T 4000T | 3000 3500 4000 | One / Two | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | H2PC- 4500, 5000, 6000 | 4500 5000 6000 | One / Two | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. |
| | H2PC- 4500T, 5000T, 6000T | 4500 5000 6000 | One / Two | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 10-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | H2PC – 750/ 750T | 780 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 2-27-2012 / 12-31-2014 | 3' of soil cover, water table at lid. Traffic rated models must have traffic rated risers and lid. |
| | H2PC – 1000/ 1000T | 1000 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 2-27-2012 / 12-31-2014 | 3' of soil cover, water table at lid. Traffic rated models must have traffic rated risers and lid. |

DOH 337-046 Page 21 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|------------------------------------|-------------------------|---------------------|------------------------|--|---------------------------|--|
| H2 Precast Inc. (continued) | H2PC – 1500/ 1500T | 1500 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 2-27-2012 / 12-31-2014 | 3' of soil cover, water table at lid. Traffic rated models must have traffic rated risers and lid. |
| | H2PC – 2000 / 2500 | 2000, 2500 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 2-27-2012 / 12-31-2014 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. |
| | H2PC – 2000T/2500T | 2000, 2500 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 2-27-2012 / 12-31-2014 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Hagerman Pre Cast P.O. Box 2842 | B-500 | 1097 | Three | BioRobix ATU | 3-7-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| Poulsbo, WA 98370 360-598-6121 | B-500-HW | 1097 | Three | BioRobix ATU | 3-7-2011 / 12-31-2013 | 3' of soil cover, groundwater to surface. |
| 360-394-9544 (fax) | 500 Trash | 511 | One | Pump Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum water table at ground level. |
| | 1000 S, P & G | 1000 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000 S-T, P- T & G-T | 1000 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 22 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|-------------------------------|-------------------------|---------------------|------------------------|--|---------------------------|--|
| Hagerman Pre Cast (continued) | 1250 S, P & G | 1261 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T, P- T & G-T | 1261 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 FAST | 1261 | Two | MicroFAST 0.5 | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 FAST – T | 1261 | Two | MicroFAST 0.5 | 8-22-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 S, P & G | 1512 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500 S-T, P- T & G-T | 1512 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 8-22-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 FAST | 1512 | Two | MicroFAST 0.5 & MicroFAST 0.75 | 8-22-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500 FAST – T | 1512 | Two | MicroFAST 0.5 & MicroFAST 0.75 | 8-22-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 23 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|----------------------|---------------------|----------------------------|---|---------------------------|---|
| Hagerman Pre Cast (continued) | M 31 | 1888 | One | Glendon BioFilter Model M-31 Basin | 8-22-2011 / 12-31-2013 | Follow installation instructions. |
| Hayes Concrete Products, Inc 19401 State Route 203 Monroe, WA 98272 | 750P-HW | 775 | One | Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| 425-788-5686 360-794-1468 (fax) hayesconcrete@earthlink.net | 1000S / 1000P | 990 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000S-HW 1000P-HW | 990 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| | 1250S / 1250P | 1228 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250S-HW 1250P-HW | 1228 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| | 1500S / 1500P | 1539 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500S-HW 1500P-HW | 1539 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| Koncrete Industries, Inc. P.O. Box 911 Walla Walla, WA 99362 509-525-9143 509-525-4031 (fax) www.koncreteindustries.com | 1250 | 1252 | Two | Septic Tank | 3-14-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. |

DOH 337-046 Page 24 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|----------------------|---------------------|------------------------|--|----------------------------|---|
| Krieg Concrete Products, Inc. 35717 State Route 20 Oak Harbor, WA 98277 360-675-2727 | 700P | 713 | One | Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, water table at ground level. Locate pumps in center of tank below access. |
| 360-675-4181 (fax) | 1000P DEL ZOTTO | 1088 | One | Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. Locate pumps in center of tank below access. |
| | 1000P DEL ZOTTO-T | 1088 | One | Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. Locate pumps in center of tank below access. |
| | 1000P | 1006 | One | Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. Locate pumps in center of tank below access. |
| | 1000P-T | 1006 | One | Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. Locate pumps in center of tank below access. |
| | 1000S / 1000G | 1006 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000S-T / 1000G-T | 1006 | Two | Septic Tank, Grease Interceptor Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 25 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|------------------------|---------------------|----------------------------|---|----------------------------|--|
| Krieg Concrete Products, Inc. (continued) | 1250P / 1250S | 1255 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. Locate pumps in center of tank below access. |
| | 1250P-HW / 1250S-HW | 1255 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | Maximum water table at ground level. Locate pumps in center of tank below access. |
| | 1500P / 1500S | 1556 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. Locate pumps in center of tank below access. |
| | 1500P-T / 1500S-T | 1556 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 11-24-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. Locate pumps in center of tank below access. |
| | DF50 | 909 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | B-500 | 1097 | Three | BioRobix ATU | 3-7-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | B-500-HW | 1097 | Three | BioRobix ATU | 3-7-2011 / 12-31-2013 | 3' of soil cover, groundwater to surface. |
| | B-500-P | 1997 | Four | BioRobix ATU /pump chamber | 3-7-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | B-500-PHW | 1997 | Four | BioRobix ATU /pump chamber | 3-7-2011 / 12-31-2013 | 3' of soil cover, groundwater to surface. |

DOH 337-046 Page 26 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|--------------------|------------------------------|----------------------------|---|--------------------------|---|
| M-1 Tanks, Inc. 13058 N. Frontage Rd. E. Moses Lake, WA 98837 | 670P | 681 | One | Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. |
| 509-766-2914 509-764-0905 (fax) m1production@yahoo.com | 1000S / 1000P | 1021 (Septic) 1039 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000S-T 1000P-T | 1021 (Septic) 1039 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250S / 1250P | 1311 (Septic) 1333 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250S-T 1250P-T | 1311 (Septic) 1333 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500S / 1500P | 1573 (Septic) 1602 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500S-T 1500P-T | 1573 (Septic) 1602 (Pump) | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 8-4-2010 / 12-31-2015 | 3' of soil cover, maximum high water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |

DOH 337-046 Page 27 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|------------------------------------|-----------------|---------------------|------------------------|--|-----------------------|---|
| Miles Sand & Gravel | JET 500 | | Two | Jet Inc. J-500 | 7-6-2010 / | 3' of soil cover, maximum |
| Company, Inc. | | | | Treatment System | 12-31-2015 | high water table to top of lid. |
| P. O. Box 130 | JET 500-HW | | Two | Jet Inc. J-500 | 7-6-2010 / | 3' of soil cover, maximum |
| Auburn, WA 98071-0130 | |] | | Treatment System | 12-31-2015 | water table at ground level. |
| 253-833-3705 | 1150S | 1165 | Two | Septic Tank, Holding | 7-6-2010 / | 3' of soil cover, maximum |
| 253-833-3746 (fax) | |] | | Tank & Trash Tank | 12-31-2015 | high water table to top of lid. |
| stevend@gravelpits.com | 1150S-HW | 1165 | Two | Septic Tank, Holding | 7-6-2010 / | 3' of soil cover, maximum |
| | |] | | Tank & Trash Tank | 12-31-2015 | water table at ground level. |
| | 1200P | 1282 | One | Pump Tank | 7-6-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | high water table to top of lid. |
| | 1200P-HW | 1282 | One | Pump Tank | 7-6-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | water table at ground level. |
| Northwest Cascade, Inc. | BZ2-1000 | 1015 | Two | Septic Tank, Holding | 7-21-2010 / | 3' of soil cover, maximum |
| P.O. Box 73399 | | | | Tank & Trash Tank | 12-31-2015 | high water table to top of lid. |
| Puyallup, WA 98373 | BZ2-1000T | 1015 | Two | Septic Tank, Holding | 7-21-2010 / | Maximum water table at |
| 253-848-2371 253-840-0877 (fax) | | | | Tank & Trash Tank | 12-31-2015 | ground level. HS20-44 traffic rating. Must have traffic |
| | DED 1000 | 1000 | | D | 7.21.2010./ | rated risers and lid. |
| | BZP-1000 | 1060 | One | Pump Tank, Holding | 7-21-2010 / | 3' of soil cover, maximum |
| | | | | Tank, Trash Tank & | 12-31-2015 | high water table to top of lid. MicroFAST Tank must |
| | | | | MicroFAST Tank | | |
| | | | | | | follow a 500 gallon settling |
| | BZP-1000T | 1000 | | D T II. II. II. | 7-21-2010 / | tank. Maximum water table at |
| | BZP-10001 | 1060 | One | Pump Tank, Holding Tank, Trash Tank & | 12-31-2015 | ground level. HS20-44 traffic |
| | | | | MicroFAST Tank | 12-31-2013 | rating. Must have traffic |
| | | | | MICIOFAST Talik | | rated risers and lid. |
| | | | | | | MicroFAST Tank must |
| | | | | | | follow a 500 gallon settling |
| | | | | | | tank. |
| | BZ2-1200 | 1133 | Two | Septic Tank, Holding | 7-21-2010 / | 3' of soil cover, maximum |
| | 522 1200 | 1133 | 10 | Tank & Trash Tank | 12-31-2015 | high water table to top of lid. |

DOH 337-046 Page 28 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|-------------------------------------|-----------------|---------------------|------------------------|--|----------------------------|---|
| Northwest Cascade, Inc. (continued) | BZ2-1200T | 1133 | Two | Septic Tank, Holding Tank & Trash Tank | 7-21-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | BZP-1200 | 1183 | One | Pump Tank, Holding Tank, Trash Tank & MicroFAST Tank | 7-21-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. MicroFAST Tank must follow a 500 gallon settling tank. |
| | BZP-1200T | 1183 | One | Pump Tank, Holding Tank, Trash Tank & MicroFAST Tank | 7-21-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. MicroFAST Tank must follow a 500 gallon settling tank. |
| | BZ2-1500 | 1574 | Two | Septic Tank, Holding Tank, Trash Tank & MicroFAST Tank | 7-21-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | BZ2-1500T | 1574 | Two | Septic Tank, Holding Tank, Trash Tank & MicroFAST Tank | 7-21-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | BZP-1500 | 1610 | One | Pump Tank, Holding Tank & Trash Tank | 7-21-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | BZP-1500T | 1610 | One | Pump Tank, Holding Tank & Trash Tank | 7-21-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | DF50 | 909 | One | Delta Whitewater DF Series | 12-10-2010 / 12-31-2015 | 3' of soil cover. Maximum water table at ground level. |
| | B-500 | 1097 | Three | BioRobix ATU | 2-15-2012 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 29 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-------------------|---------------------|----------------------------|---|---------------------------|--|
| Northwest Cascade, Inc. (continued) | B-500-HW | 1097 | Three | BioRobix ATU | 2-15-2012 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| Okanogan Valley Concrete, Inc. P.O. Box 1296 | 1000 S & P | 1066 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 09-01-11 / 12-31-13 | 3' of soil cover, maximum high water table to top of lid. |
| Okanogan, WA 98840 509-422-3211 | 1000 S-T & P-T | 1066 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 09-01-11 / 12-31-13 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 S | 1284 | Two | Septic Tank, Holding Tank & Trash Tank | 09-01-11 / 12-31-13 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250 S-T | 1284 | Two | Septic Tank, Holding Tank & Trash Tank | 09-01-11 / 12-31-13 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| Peninsula Tanks Inc. 1370 Woodcock Road Sequim, WA 98382 360-683-4714 360-681-8804 (fax) | 1000 | 1022 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank & Trash Tank | 1-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1000-T | 1022 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank & Trash Tank | 1-13-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1250 | 1259 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank, Trash Tank & MicroFAST 0.5 | 1-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |

DOH 337-046 Page 30 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|----------------------------------|-------------------|---------------------|----------------------------|--|---------------------------|--|
| Peninsula Tanks Inc. (continued) | 1250-T | 1259 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank, Trash Tank & MicroFAST 0.5 | 1-13-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 | 1561 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank, Trash Tank, MicroFAST 0.5 & 0.75 and BioBarrier 0.5 | 1-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500-T | 1561 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank, Trash Tank, MicroFAST 0.5 & 0.75 and BioBarrier 0.5 | 1-13-2011 /12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 2000 | 2083 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank & Trash Tank | 1-13-2011 / 12-31-2013 | 3' of soil cover, maximum high water table to top of lid. |
| | 2000-T | 2083 | One (Pump) Two (Septic) | Septic Tank, Pump Tank, Holding Tank, Grease Interceptor Tank & Trash Tank | 1-13-2011 / 12-31-2013 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 1500 M31 Basin | 1561 | One | Glendon BioFilter Model M-31 Basin | 1-11-2012 / 12-31-2014 | Follow installation instructions. |

DOH 337-046 Page 31 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|--|---------------------------|--|
| Rada Inc. 2707 E. Lewis Pl | 625 | 625 | One | Pump Tank, Holding Tank & Trash Tank | 10-9-2012 / 12-13-2014 | 3' of soil cover, maximum water table at ground level. |
| Pasco, WA 99301 509-547-3974 509-547-9066 (fax) | 1100 | 1108 | Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 5-7-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. |
| | 1600 | 1625 | Two / Three | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 5-7-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. |
| Rapid Readymix Co. P.O. Box 1050 | R1000 | 1017 | Two | Septic Tank, Holding Tank & Trash Tank | 5-31-2012 / 12-31-2014 | 3' of soil cover, maximum water table to top of lid. |
| Goldendale, WA 98620 509-773-5919 509-773-7868 (fax) | R1250 | 1237 | Two | Septic Tank, Holding Tank & Trash Tank | 5-31-2012 / 12-31-2014 | 3' of soil cover, maximum water table to top of lid. |
| Reese Concrete Products Mfg. Inc., 1606 S. Ely | RCP 1000 | 1043 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 5-11-2012 / 12-31-2014 | 3' of soil cover, maximum water table at ground level. |
| Kennewich, WA 99337 (509) 586-3704 (509) 586-3341 (fax) | RCP 1500 | 1592 | One / Two / Three | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 5-11-2012 / 12-31-2014 | 3' of soil cover, maximum water table at ground level. |
| Shope Concrete Products 1618 East Main Avenue Puyallup, WA 98372-3142 253-848-1551 253-845-0292 (fax) support@shopeconcrete.com | 48" – 96" MH | Depends on Depth | One | Pump Tank | 4-14-2011 / 12/31/2013 | Follow installation instructions. |

DOH 337-046 Page 32 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|-----------------------|---------------------|------------------------|---|---------------------------|--|
| Sound Placement Services PO Box 1649 | NuWater B- 500 | 1097 | Three | NuWater (BioRobix) ATU | 2-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| Castle Rock, WA 98611 360-274-7675 | NuWater B- 500-HW | 1097 | Three | NuWater (BioRobix) ATU | 2-22-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| 360-274-7391 (fax) | NuWater B- 500-P | 1997 | Four | NuWater (BioRobix) ATU /pump chamber | 2-22-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | NuWater B- 500-PHW | 1997 | Four | NuWater (BioRobix) ATU /pump chamber | 2-22-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| | 1500SR-T | 1690 | Two | Septic Tank | 4-19-2010 / 12-31-2015 | Maximum water table at ground level. HS20-44 traffic rating. Must have traffic rated risers and lid. |
| | 660P | 803 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 660P-HW | 803 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| | 1050SR | 1026 | Two | Septic Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1050SR-HW | 1026 | Two | Septic Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| | 1250P | 1275 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250P-HW | 1275 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| | 1250SR | 1250 | Two | Septic Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1250SR-HW | 1250 | Two | Septic Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |
| | 1500P | 1585 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, maximum high water table to top of lid. |
| | 1500P-HW | 1585 | One | Pump Tank | 4-28-2010 / 12-31-2015 | 3' of soil cover, groundwater to surface. |

DOH 337-046 Page 33 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--------------------------|-----------------|---------------------|------------------------|-----------------------|-----------------------|---------------------------------|
| Sound Placement Services | 1500SR | 1500 | Two | Septic Tank | 4-28-2010 / | 3' of soil cover, maximum |
| (continued) | |] | | | 12-31-2015 | high water table to top of lid. |
| | 1500SR-HW | 1500 | Two | Septic Tank | 4-28-2010 / | 3' of soil cover, groundwater |
| | |] | | | 12-31-2015 | to surface. |
| | 1800P | 1912 | One | Pump Tank | 4-28-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | high water table to top of lid. |
| | 1800P-HW | 1912 | One | Pump Tank | 4-28-2010 / | 3' of soil cover, groundwater |
| | | | | | 12-31-2015 | to surface. |
| | 12-2633 | 2250 | Three | Septic/Pump Tank | 4-28-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | high water table to top of lid. |
| | 12-2633 P- | 2250 | Three | Septic/Pump Tank | 4-28-2010 / | 3' of soil cover, groundwater |
| | HW | | | | 12-31-2015 | to surface. |
| | 2250SR | 2264 | Two | Septic Tank | 4-28-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | high water table to top of lid. |
| | 2250SR-HW | 2264 | Two | Septic Tank | 4-28-2010 / | 3' of soil cover, groundwater |
| | | | ,, | | 12-31-2015 | to surface. |
| | 2700P | 2766 | One | Pump Tank | 4-28-2010 / | 3' of soil cover, maximum |
| | | | | | 12-31-2015 | high water table to top of lid. |
| | 2700P-HW | 2766 | One | Pump Tank | 4-28-2010 / | 3' of soil cover, groundwater |
| | | | | | 12-31-2015 | to surface. |
| | 2700P-T | 2766 | One | Pump Tank | 4-28-2010 / | Maximum water table at |
| | | | | | 12-31-2015 | ground level. HS20-44 traffic |
| | | | | | | rating. Must have traffic |
| | | | | | | rated risers and lid. |
| | 2633 | 2061 | Three | Septic / Whitewater / | 12-10-2010 / | 3' of soil cover, maximum |
| | Whitewater | <u> </u> | | Pump Tank | 12-31-2015 | high water table to top of lid. |
| | 2633 | 2061 | Three | Septic / Whitewater / | 12-10-2010 / | 3' of soil cover. Maximum |
| | Whitewater – | | | Pump Tank | 12-31-2015 | water table at ground level. |
| | HW | J | | | <u> </u> | |

DOH 337-046 Page 34 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|---|--------------------------|---|
| Sound Placement Services (continued) | M31 | 1976 | One | Glendon Basin | 08-18-11 / 12-31-15 | Containment vessel / membrane for the M31 Glendon BioFilter treatment unit (120 GPD). Follow installation instructions. |
| Toners Excavating 4321 E Eloika Road Chattaroy, WA 99003 509-292-2360 509-292-8990 (fax) | 1000 | 1000 | One / Two | Septic Tank, Pump Tank, Holding Tank and Trash Tank | 6-7-2012 / 12-31-2014 | Anti-Buoyancy measures required if water table above mid tank. 3' maximum depth of burial. |
| White Block Company, Inc. 6219 East Trent Avenue | B-500 | 1097 | Three | BioRobix ATU | 6-2-2011 / 12-31-13 | 3' of soil cover, maximum high water table to top of lid. |
| Spokane Valley, WA 99212 509-534-0651 | B-500-HW | 1097 | Three | BioRobix ATU | 6-2-2011 / 12-31-13 | 3' of soil cover, groundwater to surface. |
| 509-534-0654 (fax) whiteblockcompany.com | B-500-P | 1997 | Four | BioRobix ATU / pump chamber | 6-2-2011 / 12-31-13 | 3' of soil cover, maximum high water table to top of lid. |
| | B-500-PHW | 1997 | Four | BioRobix ATU / pump chamber | 6-2-2011 / 12-31-13 | 3' of soil cover, groundwater to surface. |
| | 500 | 500 | One | Pump Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |
| | 1000 | 1000 | One/Two | Septic Tank, Pump Tank, Grease Interceptor Tank and Holding Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |
| | 1500 | 1500 | One/Two/Three | Septic Tank, Pump Tank, Grease Interceptor Tank and Holding Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |

DOH 337-046 Page 35 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|--------------------|--------------------------------|------------------------|--|--------------------------|---|
| White Block Company, Inc. (continued) | 2000 | 2000 | One/Two | Septic Tank, Pump Tank, Grease Interceptor Tank and Holding Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |
| | 2500 | 2500 | One/Two | Septic Tank, Pump Tank, Grease Interceptor Tank and Holding Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |
| | 5000 | 5000 | One | Septic Tank, Pump Tank and Holding Tank | 2-9-2012 / 12-31-2014 | 3' of soil cover, water table at ground level. Traffic rated models must have traffic rated risers and lid. |
| Wilbert Precast Inc. E 2215 Brooklyn Spokane, WA 99217 509-325-4573 509-325-5098 (fax) | 48" MH | Depends On Depth | One | Pump Tank | 12-28-11 / 12-31-13 | Uplift ring depends on depth of bury and location of water table. Traffic riser and cover required. 10' maximum bury depth. |
| | JET 500 | 1185 | Three | J-500 BAT Media systems | 12-28-11 / 12-31-13 | Anchor is required when installed in saturated soil. |
| | 500 Monolithic | 516 | One | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 12-28-11 / 12-31-13 | Uplift ring depends on depth of bury and location of water table. Traffic risers and covers required for TB models (traffic rated). |
| | 1000 Monolithic | 1084 (single) 1047 (double) | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-28-11 / 12-31-13 | Uplift ring depends on depth of bury and location of water table. Traffic risers and covers required for TB models (traffic rated). |

DOH 337-046 Page 36 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|----------------------|-----------------|---------------------|------------------------|-------------------------------------|-----------------------|---|
| Wilbert Precast Inc. | 1250 | 1297 (single) | One / Two | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| (continued) | Monolithic | 1258 (double) | | Tank, Grease | 12-31-13 | of bury and location of water |
| | | | | Interceptor Tank, | | table. Traffic risers and |
| | | | | Holding Tank & | | covers required for TB |
| | 1.500 | | | Trash Tank | | models (traffic rated). |
| | 1500 | 1646 | Multiple | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| | Monolithic | | | Tank, Grease | 12-31-13 | of bury and location of water |
| | | | | Interceptor Tank, | | table. Traffic risers and |
| | | | | Holding Tank & Trash Tank | | covers required for TB models (traffic rated). |
| | 1000 | 1047 (single) | One / Two | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| | 2 Piece Tank | 1012 (double) | Olie / Two | Tank, Grease | 12-28-117 | of bury and location of water |
| | 2 Tiece Tank | 1012 (dodole) | | Interceptor Tank, | 12 31 13 | table. Traffic risers and |
| | | | | Holding Tank & | | covers required for TB |
| | | | | Trash Tank | | models (traffic rated). |
| | 1500 | 1612 (single) | One / Two | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| | 2 Piece Tank | 1577 (double) | | Tank, Grease | 12-31-13 | of bury and location of water |
| | | | | Interceptor Tank, | | table. Traffic risers and |
| | | | | Holding Tank & | | covers required for TB |
| | | | | Trash Tank | | models (traffic rated). |
| | 2000 | 2150 (single) | One / Two | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| | 2 Piece Tank | 2103 (double) | | Tank, Grease | 12-31-13 | of bury and location of water |
| | | | | Interceptor Tank, | | table. Traffic risers and |
| | | | | Holding Tank & | | covers required for TB |
| | 2500 | 2600 (: 1) | | Trash Tank | 10.00.11./ | models (traffic rated). |
| | 2500 | 2688 (single) | One / Two | Septic Tank, Pump | 12-28-11 / | Uplift ring depends on depth |
| | 2 Piece Tank | 2629 (double) | | Tank, Grease | 12-31-13 | of bury and location of water table. Traffic risers and |
| | | | | Interceptor Tank, Holding Tank & | | covers required for TB |
| | | | | Trash Tank | | models (traffic rated). |
| | <u> </u> | J | l | I 1 a s ii 1 a ii k | <u> </u> | mouers (marric raicu). |

DOH 337-046 Page 37 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|--|------------------------|--|---------------------------|--|
| Wilbert Precast Inc. (continued) | 916 Tanks | 3000, 4000, 5000, 6000, 7000, 7800 & 8000 | Multiple | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-28-11 / 12-31-13 | Check with tank manufacturer regarding additional reinforcement. Uplift ring and wide flange installation depends on bury depth, water table location and traffic loadings. Traffic risers and covers are required in traffic areas. |
| Willamette Graystone, Inc. 3700 Franklin Blvd Eugene, OR 97403 (541) 726-7666 (541) 744-8953 (fax) | 500 | 500 | One | Pump Tank, Holding Tank & Trash Tank | 6-21-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. 30" or less of ground cover may require additional buoyancy consideration. |
| | 1000 | 1000 | One / Two | Septic Tank, Holding Tank & Trash Tank | 6-21-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. 30" or less of ground cover may require additional buoyancy consideration. |
| | 1500 | 1500 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 6-21-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. 30" or less of ground cover may require additional buoyancy consideration. |
| | 2000 | 2000 | One / Two | Septic Tank, Holding Tank & Trash Tank | 6-21-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. 30" or less of ground cover may require additional buoyancy consideration. |
| | 3000 | 3000 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 6-21-2012 / 12-31-2014 | 4' of soil cover, maximum water table at ground level. 30" or less of ground cover may require additional buoyancy consideration. |

DOH 337-046 Page 38 of 47

List of Manufacturers of Registered Sewage Tanks – Non-Concrete Tanks

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|------------------------------|-----------------|---------------------|------------------------|------------------------|-----------------------|---|
| Clarus Environmental | ZF-450 | 450 | Three | Fusion Wastewater | 9-10-2012 / | Follow installation |
| 3649 Cane Run Road | | | | Treatment System | 12-31-2014 | instructions. |
| Louisville, KY 40211 | ZF-600 | 600 | Three | Fusion Wastewater | 9-10-2012 / | Follow installation |
| 800-928-7867 | | | | Treatment System | 12-31-2014 | instructions. |
| 502-774-3624 (fax) | ZF-800 | 800 | Three | Fusion Wastewater | 9-10-2012 / | Follow installation |
| www.clarusenvironmental.com | | | | Treatment System | 12-31-2014 | instructions. |
| Tank Material: Fiberglass | | | | | | |
| Containment Solutions, Inc. | SWT D6 (6') | 2000 to 6000 | Multiple | Septic Tank, Pump | 5-1-2012 / | Follow installation |
| 5150 Jefferson Chemical Road | , | | 1 | Tank and Holding | 12-31-2014 | instructions and design |
| Conroe, TX 77301 | | | | Tank | | criteria. Anti-Buoyancy |
| 800-537-4730 | | | | | | measures required if tank is |
| 800-839-4272 (fax) | | | | | | submerged under water. |
| www.containmentsolutions.com | SWT G6 (8') | 4000 to | Multiple | Septic Tank, Pump | 5-1-2012 / | Follow installation |
| | | 15,000 | | Tank and Holding | 12-31-2014 | instructions and design |
| | | | | Tank | | criteria. Anti-Buoyancy |
| Tank Material: | | | | | | measures required if tank is |
| Fiberglass | | 10.000 | N. 1.1.1 | C . T 1 D | 7 1 2012 / | submerged under water. |
| | SWT D6 | 10,000 to | Multiple | Septic Tank, Pump | 5-1-2012 / | Follow installation |
| | (10') | 40,000 | | Tank and Holding | 12-31-2014 | instructions and design |
| | | | | Tank | | criteria. Anti-Buoyancy |
| | | | | | | measures required if tank is submerged under water. |
| | SWT D7 | 25,000 to | Multiple | Septic Tank, Pump | 5-1-2012 / | Follow installation |
| | (12') | 40,000 | Munibic | Tank and Holding | 12-31-2014 | instructions and design |
| | (12) | 70,000 | | Tank and Holding Tank | 12-31-2014 | criteria. Anti-Buoyancy |
| | | | | 1 and | | measures required if tank is |
| | | | | | | submerged under water. |

DOH 337-046 Page 39 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|-------------------|-----------------------|--|
| Ecological Tanks, Inc. | AS500 | 1000 | | Aqua Safe AS500 | 9-27-2010 / | Maximum amount of cover |
| 2247 Hwy. 151 North | | | | | 12-31-2015 | should be no greater than 18". |
| Downsville, LA 71234 | | | | | | No ground water. |
| 318-644-0397 | AS600 | 1190 | | Aqua Safe AS600 | 9-27-2010 / | Maximum amount of cover |
| 318-644-7257 (fax) aquasafe@bayou.com | | | | | 12-31-2015 | should be no greater than 18". No ground water. |
| | AS750 | 1516 | | Aqua Safe AS750 | 9-27-2010 / | Maximum amount of cover |
| Tank Material: Fiberglass | | | | | 12-31-2015 | should be no greater than 18". No ground water. |
| | AS1000 | 2008 | | Aqua Safe AS1000 | 9-27-2010 / | Maximum amount of cover |
| | | | | | 12-31-2015 | should be no greater than 18". |
| | | | | | | No ground water. |
| | AS1500 | 2918 | | Aqua Safe AS1500 | 9-27-2010 / | Maximum amount of cover |
| | | | | | 12-31-2015 | should be no greater than 18". No ground water. |
| | AS500L | 908 | | Aqua Safe AS500L | 9-27-2010 / | Maximum amount of cover |
| | | | | • | 12-31-2015 | should be no greater than 18". |
| | | |] | | | No ground water. |
| | AS600L | 1058 | | Aqua Safe AS600L | 9-27-2010 / | Maximum amount of cover |
| | | | | | 12-31-2015 | should be no greater than 18". No ground water. |
| | AS800L | 1516 | | Aqua Safe AS800L | 9-27-2010 / | Maximum amount of cover |
| | | | | | 12-31-2015 | should be no greater than 18". No ground water. |
| | AS1100L | 2008 | | Aqua Safe AS1100L | 9-27-2010 / | Maximum amount of cover |
| | | | | • | 12-31-2015 | should be no greater than 18". |
| | | | | | | No ground water. |
| | AS600+4NR | 908 | | Aqua Safe | 9-27-2010 / | Maximum amount of cover |
| | | | | AS600+4NR | 12-31-2015 | should be no greater than 18". |
| | | | | | | No ground water. |
| | AS600+5NR | 1000 | | Aqua Safe | 9-27-2010 / | Maximum amount of cover |
| | | | | AS600+4NR | 12-31-2015 | should be no greater than 18". |
| | | | | | | No ground water. |

DOH 337-046 Page 40 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|--|----------------------------|---|
| HD Fowler Co. 13440 SE 30 th Street Bellevue WA 98005 425-746-8400 425-641-8885 (fax) www.hdfowler.com | PM-120 | | One | Glendon Basin | 2-18-2011 / 12-31-2013 | Containment vessel / membrane for the M31 Glendon BioFilter treatment unit (120 GPD). Follow installation instructions. |
| Tank Material: Polyethylene | | | | | | |
| Infiltrator Systems Inc. 6 Business Park Road Old Saybrook, CT 06475 1-800-221-4436 860-577-7001 (fax) www.infiltratorsystems.com dlentz@infiltratorsystems.net Tank Material: Polyethylene Polypropylene | IM-1060 | 1070 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank, Trash Tank and MicroFast Treatment Units | 4-7-2011 / 12-31-2013 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| | TW-300 | 313 | One | Pump Tank, Trash Tank, Holding Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| | TW-500 | 503 | One | Pump Tank, Trash Tank, Holding Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| | TW-900 | 915 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |

DOH 337-046 Page 41 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|--------------------|---------------------|------------------------|--|----------------------------|---|
| Infiltrator Systems Inc. (continued) | TW-1050 | 1052 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| | TW-1250 | 1254 | One / Two | Septic Tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| | TW-1500 | 1523 | One / Two | Septic Tank, Pump Tank, Holding Tank & Trash Tank | 10-13-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table 18" or more above tank bottom. 4' maximum depth of burial. |
| Norweco, Inc. 220 Republic Street Norwalk, OH 44857-1196 419-668-4471 419-663-5440 (fax) www.norweco.com | Singulair Green | 1300 | Three | Singulair Wastewater Treatment System 960-500 & TNT-500 | 2-23-2011 / 12-31-2013 | Follow installation instructions. |
| Tank Material: Polyethylene | | | | | | |

DOH 337-046 Page 42 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|---------------------|---------------------|------------------------|---------------------------------|---------------------------|---|
| Norwesco, Inc. and Snyder Industries 4365 Steiner Street PO Box 439 St. Bonifacius, MN | 1000 Low Profile | 1002 | Two | Septic Tank and Holding Tank | 7-8-2011 / 12-31-2013 | Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| 55375-0439 800-446-8817 800-874-2371 (fax) www.norwesco.com | 1250 Low Profile | 1263 | Two | Septic Tank and Holding Tank | 7-8-2011 / 12-31-2013 | Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| Tank Material: Polyethylene | 1500 Low Profile | 1504 | Two | Septic Tank and Holding Tank | 7-8-2011 / 12-31-2013 | Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 300 Sphere | 311 | One | Pump Tank and Holding Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 500 Sphere | 513 | One | Pump Tank and Holding Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |

DOH 337-046 Page 43 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|---|---------------------------|---|
| Norwesco, Inc. and Snyder Industries (continued) | 1000 Legacy | 1031 | Two | Septic Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 1250 Legacy | 1250 | Two | Septic Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 1500 Legacy | 1500 | Two | Septic Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 1000 Bruiser | 1031 | One / Two | Septic Tank, Pump Tank and Holding Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |

DOH 337-046 Page 44 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|---|-----------------|----------------------|------------------------|--|---------------------------|---|
| Norwesco, Inc. and Snyder Industries (continued) | 1250 Bruiser | 1250 | One / Two | Septic Tank, Pump Tank and Holding Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| | 1500 Bruiser | 1500 | One / Two | Septic Tank, Pump Tank and Holding Tank | 4-30-2012 / 12-31-2014 | 6" minimum cover and 30" maximum cover. Follow installation instructions and design criteria. Anti-Buoyancy measures required if tank is submerged under water. |
| Orenco Systems, Inc. 814 Airway Avenue Sutherlin, OR 97479-9012 | AX-MAX | Depends on Length | Multiple | AdvanTex AX-MAX Treatment System | 5-16-2011 / 12-31-2013 | Follow installation instructions and design criteria. |
| 541-459-4449 541-459-2884 (fax) www.orenco.com | 1000 | 1050 | Multiple | Septic Tank, Pump Tank, Grease Interceptor Tank, Trash Tank & Holding Tank | 1-25-2012 / 12-31-2014 | 4' maximum burial depth. Follow installation instructions and design criteria. Antibuoyancy measures may be required. |
| Fiberglass | 1500 | 1570 | Multiple | Septic Tank, Pump Tank, Grease Interceptor Tank, Trash Tank & Holding Tank | 1-25-2012 / 12-31-2014 | 4' maximum burial depth. Follow installation instructions and design criteria. Antibuoyancy measures may be required. |
| | 2000 | 2078 | Multiple | Septic Tank, Pump Tank, Grease Interceptor Tank, Trash Tank & Holding Tank | 1-25-2012 / 12-31-2014 | 4' maximum burial depth. Follow installation instructions and design criteria. Antibuoyancy measures may be required. |

DOH 337-046 Page 45 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------------------|---------------------|------------------------|--|---------------------------|--|
| Orenco Systems, Inc. (continued) | AX-RT-1000 | 1000 | Multiple | AdvanTex AX-RT Treatment Tank | 1-25-2012 / 12-31-2014 | 4' maximum burial depth. Follow installation instructions and design criteria. Antibuoyancy measures may be required. |
| | 24 & 30 Inch Pump Basins | Varies | One | Pump Tank | 11-1-2012 / 12-31-2014 | 12' maximum burial depth. Follow installation instructions and design criteria. Antibuoyancy measures may be required. |
| Premier Plastics Inc. 8328 River Way Delta B.C. Canada V4G 1C4 1-800-661-4473 604-952-6686 | 1500 EH | 1845 | Two | Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank | 4-27-2010 / 12-31-2015 | Anti-buoyancy measures required if water table submerges tank bottom >24". 4' maximum depth of burial. |
| 604-952-6696 (fax) www.premierplastics.com office@premierplastics.com | 1000 MDPE | 1000 | One / Two | Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank | 8-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above tank bottom. 4' maximum depth of burial. |
| | 1300 MDPE | 1300 | One / Two | Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank | 8-19-2010 / 12-31-2015 | Anti-Buoyancy measures required if water table above tank bottom. 4' maximum depth of burial. |

DOH 337-046 Page 46 of 47

| Manufacturer | Model Number | Tank Size (gallons) | Number of Compartments | Usage | Approved / Renewal | Limitations |
|--|-----------------|---------------------|------------------------|--|---------------------------|---|
| Xerxes Corporation 7901 Xerxes Avenue South Minneapolis, MN 55431 | 10' SWT | 25,000 (Nominal) | Multiple | Septic / Pump Tank | 6-16-2011 / 12-31-2013 | Follow installation instructions and design criteria. |
| 952-887-1890 952-887-1870 (fax) www.xerxes.com Tank Material: Fiberglass | SWT6' | 1,500 – 6,000 | Multiple | Septic tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-29-11 / 12-31-13 | Follow installation instructions and design criteria. Anti-Flotation calculations are required when groundwater is present. |
| | SWT8' | 2,000 – 15,000 | Multiple | Septic tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-29-11 / 12-31-13 | Follow installation instructions and design criteria. Anti-Flotation calculations are required when groundwater is present. |
| | SWT10' | 10,000 – 40,000 | Multiple | Septic tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-29-11 / 12-31-13 | Follow installation instructions and design criteria. Anti-Flotation calculations are required when groundwater is present. |
| | SWT12' | 20,000 – 50,000 | Multiple | Septic tank, Pump Tank, Grease Interceptor Tank, Holding Tank & Trash Tank | 12-29-11 / 12-31-13 | Follow installation instructions and design criteria. Anti-Flotation calculations are required when groundwater is present. |

DOH 337-046 Page 47 of 47